

# Produkt datablad

## HO 39 W/865

LUMILUX T5 HO | Tubular fluorescent lamps 16 mm, high output, with G5 base



- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks
- Outdoor applications only in suitable luminaires

- Excellent luminous flux
- Up to 20 % more economical than LUMILUX T8
- Up to 50 % smaller volume than comparable T8 lamps

### Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Long average lifetime: up to 24,000 h (with QUICKTRONIC ECG)
- Good color rendering group: 1B (R<sub>a</sub> : 80...89)
- Dimmable

### Product benefits

- Excellent luminous flux
- Up to 20 % more economical than LUMILUX T8
- Up to 50 % smaller volume than comparable T8 lamps



## Produkt datablad

---

### Areas of application

- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks
- Outdoor applications only in suitable luminaires

## Teknisk data


### Elektriske data

ZLDV_Nominal voltage [AGGR]	230 V
ZLDV_Nominal wattage [AGGR]	38.00 W
ZLDV_Rated lamp efficacy (HF data 25 °C) [AGGR]	75 lm/W
ZLDV_Rated wattage [AGGR]	38.00 W

### Photometrical data

ZLDV_Color rendering index Ra [AGGR]	≥80
ZLDV_Rated luminous flux [AGGR]	2850 lm
ZLDV_Luminous flux at 25 °C [AGGR]	2850 lm
ZLDV_Luminous flux at 35 °C [AGGR]	3325 lm
ZLDV_Light color [AGGR]	865
ZLDV_Rated color temperature [AGGR]	6500 K
ZLDV_Nominal luminous flux [AGGR]	2850 lm
ZLDV_Light color (designation) [AGGR]	LUMILUX Cool Daylight
ZLDV_Rated LLMF at 2,000 h [AGGR]	0.95
ZLDV_Rated LLMF at 4,000 h [AGGR]	0.93
ZLDV_Rated LLMF at 6,000 h [AGGR]	0.92
ZLDV_Rated LLMF at 8,000 h [AGGR]	0.90
ZLDV_Rated LLMF at 12,000 h [AGGR]	0.90
ZLDV_Rated LLMF at 16,000 h [AGGR]	0.90
ZLDV_Rated LLMF at 20,000 h [AGGR]	0.89

### Mål og vekt



ZLDV_Tube diameter [AGGR]	16 mm
ZLDV_Length [AGGR]	849.0 mm

## Produkt datablad

ZLDV_Length with base excl. base pins/connection [AGGR]	849.00 mm
ZLDV_Diameter [AGGR]	16.0 mm
ZLDV_Maximum diameter [AGGR]	16.0 mm

### Temperatures & operating conditions

ZLDV_Rated ambient temp.w.max.luminous flux [AGGR]	35.0 °C
--	---------

### Levetid

ZLDV_Service life [AGGR]	19000 h <sup>1)</sup>
ZLDV_Lifespan [AGGR]	24000 h <sup>1)</sup>
ZLDV_Rated lamp survival factor at 2,000 h [AGGR]	0.99
ZLDV_Rated lamp survival factor at 4,000 h [AGGR]	0.99
ZLDV_Rated lamp survival factor at 6,000 h [AGGR]	0.99
ZLDV_Rated lamp survival factor at 8,000 h [AGGR]	0.99
ZLDV_Rated lamp survival factor at 12,000 h [AGGR]	0.99
ZLDV_Rated lamp survival factor at 16,000 h [AGGR]	0.97
ZLDV_Rated lamp survival factor at 20,000 h [AGGR]	0.85
ZLDV_Operation mode LLMF/LSF [AGGR]	HF
ZLDV_Rated lamp life time [AGGR]	24000 h

<sup>1)</sup> With preheat ECG

### Ytterligere produktdata

ZLDV_Base (standard designation) [AGGR]	G5
ZLDV_Mercury content [AGGR]	1.7 mg
ZLDV_Product remark [AGGR]	Suitable for ECG operation only/Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C
Appropriate disposal acc. to WEEE	Ja

### Egenskaper

ZLDV_Dimmable [AGGR]	Yes
ZLDV_Suitable for indoor [AGGR]	Yes


### Sertifikater og standarder

ZLDV_Energy efficiency class [AGGR]	A
ZLDV_Energy consumption [AGGR]	42 kWh/1000h

## Produkt datablad

### Lysfordeling

---




Spectral power distribution

---

### Systemgaranti

OSRAM-system+garanti i kombinasjon med OSRAM ECG-er



Circuit diagram



Circuit diagram

---

### Logistikk data

Product kode	Produkt beskrivelse	Forpakkings enhet (stk/enhet)	Dimensjoner (lengde x bredde x høyde)	Volum	Brutto vekt
--------------	---------------------	-------------------------------	---------------------------------------	-------	-------------

## Produkt datablad

4050300453514	HO 39 W/865	NO: VS 40	900 mm x 92 mm x 194 mm	16.06 dm <sup>3</sup>	4054.00 g
4050300591681	HO 39 W/865	NO: VS 20	882 mm x 83 mm x 104 mm	7.61 dm <sup>3</sup>	2280.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Referanser / Lenker

For mer informasjon om systemgarantien samt vilkårene og betingelsene i garantien besøk

▶ [www.osram.com/system-guarantee](http://www.osram.com/system-guarantee)

### Ansvarsfraskrivelse

Endres uten varsel. Sørg alltid for å bruke den nyeste versjonen.

OSRAM GMBH is distribution partner  
of LEDVANCE for Digital Lighting  
Systems and Components

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany

## HO 39 W/865

LUMILUX T5 HO | Tubular fluorescent lamps 16 mm, high output, with G5 base

Produktnavn	Produktnavn ECG	EAN	Nominal wattage + Power loss	Nominell strøm	Lysstrøm ved 35 ° C	Antall belysnings utganger
HO 39 W/865	QT-FIT 5/8 1x18-39	4008321873927	42.00 W	0.19 A	3100 lm	1
	QT-FIT 5/8 2x18-39	4008321873903	80.00 W	0.36 A	3100 lm	2
	QTi 1x14/24/21/39 GII	4008321383334	41.00 W	0.18 A	3100 lm	1
	QTi 1x21/39 DIM	4050300870564	41.80 W	0.18 A	3100 lm	1
	QTi 2x14/24/21/39 GII	4008321383396	81.00 W	0.36 A	3100 lm	2
	QTi 2x21/39 DIM	4050300870694	82.00 W	0.36 A	3100 lm	2
	QTi DALI 1x21/39 DIM	4050300870366	41.80 W	0.18 A	3100 lm	1
	QTi DALI 2x21/39 DIM	4050300870489	82.00 W	0.36 A	3100 lm	2
	QTP-M 1x26-42	4008321329134	41.00 W	0.18 A	3100 lm	1
	QTP-OPTIMAL 1x18-40	4008321873743	41.00 W	0.13 A	3100 lm	1
QTP-OPTIMAL 2x18-40	4008321873767	88.00 W	0.24 A	3100 lm	2	